


ARG-WL8-EXP**wireless expander module**

The wireless expander module compatible with ARG-WL8-TRV wireless translator module. The unit provides a convenient method to increase radiocommunication range beyond that possible from a single translator by relaying the radio communication to further expanders or directly to the wireless field devices. This functionality makes it possible to build large fully wireless systems or add wireless devices into areas where cabling for translators is difficult or impossible. All expanders are fully monitored ensuring the highest levels of life safety and reliability are maintained.



Using well-proven wireless technology and an orthogonal antenna design ensures the highest levels of life safety and system reliability.

Features and benefits

- Dynamic routing for all expanders and field devices
- Bi-directional wireless communication
- Compatible with up to 256 field devices
- Supports full device intelligence
- Proven wireless technology
- 5 years product warranty

Technical specifications

Power supply range	9 - 27 Vdc
Communication range with the translator or expander (open space)	2000 m
Communication range with the wireless field devices (open space)	1200 m
Operating frequency	868 MHz
Modulation type	FSK
Operating frequency channels	6
Dimensions	210 mm x 145 mm x 40 mm
Weight	400 g
IP rating	IP41
Max tolerated humidity (no condensing)	95% RH
Operating temperature range	From -30 °C to +55 °C

Warranty

All devices are supplied with the benefit of a limited 5 years warranty (the warranty period does not apply to batteries). This warranty is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.