

WL8-V**Wireless Voice Annunciator**

The wireless voice annunciator WL8-V provides voice alarm notifications in the event of fire or other emergency conditions.

WL8-V is compatible with ARGUS SPECTRUM control panels. During an alarm event, the voice annunciator receives activation commands wirelessly from the control panel directly or through compatible translator and expander modules, playing the configured voice message.

**Features and benefits**

- Bi-directional wireless communication
- Fully intelligent
- Voice synchronization with other voice annunciators
- 10 years of battery life
- Self-optimizing wireless frequency and amplitude algorithms
- 5 years product warranty

Technical specifications

Communication range with the translator or expander (open space)	1200 m
Operating frequency	868 MHz
Modulation type	FSK
Operating frequency channels	6
Sound pressure level	90 dB
Battery life:	
Primary battery (type CR123A)	8 – 10 years
Secondary battery (type CR123A)	6 – 12 months
Dimensions (Including adaptor wall base)	180 mm x 57 mm
Weight	500 g
IP rating	IP40
Max tolerated humidity (no condensing)	95% RH
Operating temperature range	From –30 °C to +55 °C

Warranty

All devices are supplied with the benefit of a limited 5 years warranty (the warranty period does not apply to batteries). This warranty is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.