

ARG-WL8Ex-CP**Wireless intrinsically safe manual call point**

The wireless intrinsically safe manual call point is a fully intelligent device which is compatible with all Streletz Translator and Expander Modules. The unit has a resettable plastic element, which displays a drop down warning flag when operated. A key is supplied with the MCP for reset and case opening.

Communication between the detector and the translator / expander modules is wireless.

**Features and benefits**

- Bi-directional wireless communication
- IEC classification: 0Ex ia IIC T6 Ga X / Ex ta ia IIIC T(200)50°C Da X
- Self-optimizing wireless frequency and amplitude algorithms
- 10 years of battery life
- 5 years product warranty

Technical specifications

Communication range with the translator or repeater (open space)	1200 m
Operating frequency	868 MHz
Modulation type	FSK
Operating frequency channels	6
Battery life:	
Primary battery (type CR123A)	8-10 years
Secondary battery (type CR2032)	6-12 months
Dimensions (Including adaptor wall base)	117 mm x 106 mm x 49 mm
Weight	200 g
IP rating	IP66
Max tolerated humidity (no condensing)	95% RH
Operating temperature range	From -30 °C to +55 °C

Warranty

All devices are supplied with the benefit of a limited 5 years warranty. This warranty (the warranty period does not apply to battery) is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.

www.argusspectrum.com