

Brelok-PRO**wireless key fob**

The wireless key fob is used to quickly arm and disarm the panel and perform other functions such as panic etc.

Using well-proven wireless technology ensures the highest levels of life safety and system reliability. The key fob operates as part of the integrated security system "Streletz-Integral", communicating with the translator or expander via the Streletz bi-directional protocol.

**Features and benefits**

- 4 buttons, 12 combinations of clicks
- Bi-directional wireless communication
- Self-optimizing wireless frequency and amplitude algorithms
- 5 years product warranty

Technical specifications

Communication range with the translator or expander (open space)	1200 m
Operating frequency	868 MHz
Modulation type	FSK
Operating frequency channels	6
Battery life (rechargeable battery):	
Primary battery (type CR2032A)	5 years
Secondary battery (type CR2032A)	6 months
Dimensions	70 mm x 34 mm x 17 mm
Weight	50 g
Max tolerated humidity (no condensing)	93% RH
Operating temperature range	from -10 °C to +55 °C

Warranty

All devices are supplied with the benefit of a limited 5 years warranty (the warranty period does not apply to battery). This warranty is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.