

SL-CP/EE, SL-CP/SE, SL-CP/FS**Intelligent Colored Manual Call Points**

The manual call points SL-CP/EE (green), SL-CP/SE (orange) and SL-CP/FS (yellow) are fully intelligent devices which are compatible with WL8-PNL3 and A240-SL control panels. In case of alarm the sounder is activated by the control panel.

The unit has a resettable plastic element. A key is supplied with the MCP for reset and case opening.

- SL-CP/EE (green) – emergency door release
- SL-CP/SE (orange) – smoke & vent control
- SL-CP/FS (yellow) – suppression system activation

**Features and benefits**

- Fully intelligent
- Resettable element
- Integrated short-circuit isolator
- Auto-addressing or via handheld programmer
- Bi-color status indicator
- 1 year product warranty

Technical specifications

Address range	From 1 to 240
Power supply (via loop)	10 – 40 V
Current consumption from the loop:	
Standby mode	150 uA
Alarm mode (depending on brightness)	6 mA
Dimensions	118 mm x 106 mm x 49 mm
Weight	210 g
IP rating	IP41
Max tolerated humidity (no condensing)	93% RH
Operating temperature range	from -30 °C to +55 °C

Warranty

All devices are supplied with the benefit of a limited 5 years warranty. This warranty is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.