

ARG-WL8-CP**wireless colored manual call point**

The wireless manual call point is a fully intelligent device which is compatible with all Streletz Translator and Expander Modules. The unit has a resettable plastic element, which displays a drop down warning flag when operated. A key is supplied with the MCP for reset and case opening.

Communication between the detector and the translator / repeater modules is wireless, via the Streletz bi-directional protocol.



- Green – emergency door release
- Orange – smoke & vent control
- Yellow – suppression system activation

Features and benefits

- Bi-directional wireless communication
- Fully intelligent
- 10 years of battery life
- Self-optimizing wireless frequency and amplitude algorithms
- High reliability
- 5 years product warranty

Technical specifications

| | |
|--|-------------------------|
| Communication range with the translator or repeater (open space) | 1200 m |
| Operating frequency | 868 MHz |
| Modulation type | FSK |
| Operating frequency channels | 6 |
| Battery life: | |
| Primary battery (type CR123A) | 8-10 years |
| Secondary battery (type CR2032) | 6-12 months |
| Dimensions | 117 mm x 106 mm x 49 mm |
| Weight | 200 g |
| IP rating | IP66 |
| Max tolerated humidity (no condensing) | 95% RH |
| Operating temperature range | From -30 °C to +55 °C |
| Communication range with the translator or repeater (open space) | 1200 m |

Warranty

All devices are supplied with the benefit of a limited 5 years warranty (the warranty period does not apply to batteries). This warranty is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.