

WL8-CP (Ex)
Wireless Intrinsically Safe Manual Call Point

The wireless manual call point WL8-CP (Ex) provides manual activation of an alarm in the event of fire or other emergency conditions. The resettable plastic element displays a warning flag when the unit is operated, and a supplied key is used for resetting the device and opening the housing.

WL8-CP (Ex) is compatible with ARGUS SPECTRUM control panels. Alarm signals are transmitted wirelessly to the control panel directly or through compatible translator and expander modules, triggering the alarm.

The intrinsically safe design of WL8-CP (Ex) enables its use in hazardous areas where intrinsically safe equipment is required.


Features and benefits

- Bi-directional wireless communication
- IEC classification: 0Ex ia IIC T6 Ga X / Ex ta ia IIIC T(200)50°C Da X
- Self-optimizing wireless frequency and amplitude algorithms
- 10 years of battery life
- 1 year product warranty

Technical specifications

Communication range with the translator or repeater (open space)	1200 m
Operating frequency	868 MHz
Modulation type	FSK
Operating frequency channels	6
Battery life:	
Primary battery (type CR123A)	8 – 10 years
Secondary battery (type CR2032)	6 – 12 months
Dimensions (Including adaptor wall base)	117 mm x 106 mm x 49 mm
Weight	200 g
IP rating	IP66
Max tolerated humidity (no condensing)	95% RH
Operating temperature range	From –30 °C to +55 °C

Warranty

All devices are supplied with the benefit of a limited 5 years warranty. This warranty (the warranty period does not apply to battery) is invalidated by mechanical or electrical damage caused in the field by incorrect handling or usage. Product must be returned via your authorized supplier for repair or replacement together with full information on any problem identified.